
DF 600/800 Eco







DF 800/600 ECO

DF ECO	800	600
Housing Ø (mm)	790	650
Blade Ø (mm)	750	600
Dim. A/B (mm)	880/830	750/680
Dim. C/D (mm)	260/920	270/770
Power motor (W)	123	123
Voltage (V/Hz)	220-240/~50	
No. of speeds	3	
Rev. max. (RPM)	870	870
Air delivery (m³/h)	15,650	13,000
Weight (kg)	19.3	16.3

Our workaholics: robust and powerful

Drum fan series with high air volume. Ideal for use in production, warehouse and logistic areas.

speeds selectable by push button switch.

Vertical grade in 360° range adjustable. Housing, blades, protective grillle and tubular steel frame matt black finish. Stable, tilt-free tubular steel frame with transport wheels and rubber feet.

Useful transport handles at the housing and cable coil at the back side of protective grille.

High-performance aluminium blade. Protection class IP44 splash water protection. 2.5 m supply cable, oil-resistant, rubber-insulated cable H05RN-F G 3 1.0 mm² with Schuko plug.



Optional 5- speed transformer ETWZ 1,0 #891020 for regulation in between a whisper quiet breeze and high performance available.

Product	Code No.	Housing/Grille Finish	Blade Finish
DF800 ECO	308085	Matt black	Aluminium, matt black
DF600 ECO	306080	Matt black	Aluminium, matt black